

Heating



**Dragons Breath Solar**

Off-grid solar battery energy suppliers

# therma**blend**-TX

**Ready to use – diluted fluid.**

Contains Ultra-high Performance Organic Acid Based Inhibitor

# Heating

## Before Use

Pipework should be clean of particulate and bacterial contamination before commissioning. When cleaning a system, it is strongly recommended that Serviceblend PRE is used. (BSRIA BG29/2012)

Installations must be designed as closed circuits to avoid contact with atmospheric oxygen which will accelerate the consumption of inhibitors and shorten the effective life of Thermablend TX.

## Dosing

As Thermablend TX Ready-To-Use is diluted at a 35% Thermablend TX to 65% de-mineralised water solution, the fluid can simply be added to your system.

## Additional Guidance

DO NOT mix Thermablend TX with other coolants, inhibitor compatibility may cause damage to the system. Thermablend TX contains corrosion inhibitors to reduce any potential system degradation, promoting higher thermal efficiency.

Blended strongly advise using Serviceblend PUR when diluting neat product. Using water with high levels of calcium salts or chlorides should be avoided.

## Uses

Suitable for solar thermal systems where gases/air have been effectively vented from the closed loop system.

## Blending Guide for Thermablend TX

Volume %	Freeze Point °C
35%	-19.6°C

## Shelf Life

Up to 3 years (original sealed container, avoid direct sunlight).



## Additional Safety Information

Follow QR code for our online SDS.

Concentration % (v/v):	Blend Date:
Client:	Purchase Order No.:

KEEP OUT OF REACH OF CHILDREN - INDUSTRIAL USE ONLY

Contains Bitrex, helping to protect children and animals.

Blended Products Limited  
Elsham Wold Industrial Estate  
Brigg, North Lincolnshire  
+44 (0) 1652 680555